

BS&B Safety Systems
K_R (Left of Slash)/Minimum Net Flow Area (Right of Slash)
Minimum Net Flow Area (MNFA) in Square Inches

Style	Media	Size																		
		0.5"	0.6875"	0.75"	1.0"	1.5"	2.0"	3.0"	4.0"	6.0"	8.0"	10.0"	12.0"	14.0"	16.0"	18.0"	20.0"	24.0"	30.0"	36.0"
B, BR, BRR	Liquid	1.47/0.18			1.47/0.80	1.47/1.76	1.47/3.33	1.47/6.51	1.47/11.8	1.47/28.8	1.47/49.8	1.47/78.8	1.47/112.0	1.47/137.0	1.47/182.0	1.47/233.0	1.47/291.0	1.47/424.0	1.47/671.0	1.47/975.0
B, BR, BRR	Gas	0.71/0.18			0.71/0.80	0.71/1.76	0.23/3.33	0.71/6.51	0.71/11.8	0.71/28.8	0.71/49.8	0.71/78.8	0.71/112.0	0.71/137.0	0.71/182.0	0.71/233.0	0.71/291.0	0.71/424.0	0.71/671.0	0.71/975.0
B-,BR-, BRR-LTF ^(Note 5)	Liquid	8.0/0.18			8.0/0.80	8.0/1.76	8.0/3.33	8.0/6.51	8.0/11.8	8.0/28.8	8.0/49.8	8.0/78.8	8.0/112.0	8.0/137.0	8.0/182.0	8.0/233.0	8.0/291.0	8.0/424.0	8.0/671.0	8.0/975.0
B-,BR-, BRR-LTF ^(Note 5)	Gas	8.0/0.18			8.0/0.80	8.0/1.76	8.0/3.33	8.0/6.51	8.0/11.8	8.0/28.8	8.0/49.8	8.0/78.8	8.0/112.0	8.0/137.0	8.0/182.0	8.0/233.0	8.0/291.0	8.0/424.0	8.0/671.0	8.0/975.0
BV-,BRV-,BSV-,BRSV-LTF ^(Note 5)	Liquid				2.47/0.57	2.47/1.44	2.47/2.24	2.47/5.41	2.47/9.62	2.47/23.7	2.47/44.1	2.47/70.8	2.47/101.0	2.47/130.0	2.47/176.0	2.47/202.0	2.47/279.0	2.47/380.0	2.47/615.0	2.47/927.0
BV-,BRV-,BSV-,BRSV-LTF ^(Note 5)	Gas				2.47/0.57	2.47/1.44	2.47/2.24	2.47/5.41	2.47/9.62	2.47/23.7	2.47/44.1	2.47/70.8	2.47/101.0	2.47/130.0	2.47/176.0	2.47/202.0	2.47/279.0	2.47/380.0	2.47/615.0	2.47/927.0
BV-,BRV-,BSV-,BRSV-LTF (w/liners) ^(Note 5)	Liquid				2.47/0.57	2.47/1.44	2.47/2.24	2.47/5.41	2.47/9.62	2.47/23.7	2.47/44.1	2.47/70.8	2.47/101.0							
BV-,BRV-,BSV-,BRSV-LTF (w/liners) ^(Note 5)	Gas				2.47/0.57	2.47/1.44	2.47/2.24	2.47/5.41	2.47/9.62	2.47/23.7	2.47/44.1	2.47/70.8	2.47/101.0							
B-Series w/liner ^(Note 3)	Liquid	1.47/0.18			1.47/0.80	1.47/1.76	1.47/3.33	1.47/6.51	1.47/11.8	1.47/28.8	1.47/49.8	1.47/78.8	1.47/112.0							
B-Series w/liner ^(Note 3)	Gas	0.71/0.18			0.71/0.80	0.71/1.76	0.71/3.33	0.71/6.51	0.71/11.8	0.71/28.8	0.71/49.8	0.71/78.8	0.71/112.0							
BV-Series ^(Note 3)	Liquid				2.45/0.57	2.45/1.44	2.45/2.24	2.45/5.41	2.45/9.62	2.45/23.7	2.45/44.1	2.45/70.8	2.45/101.0	2.45/130.0	2.45/176.0	2.45/202.0	2.45/279.0	2.45/380.0	2.45/615.0	2.45/927.0
BV-Series ^(Note 3)	Gas				0.80/0.57	0.80/1.44	0.55/2.24	0.80/5.41	0.80/9.62	0.80/23.7	0.80/44.1	0.80/70.8	0.80/101.0	0.80/130.0	0.80/176.0	0.80/202.0	0.80/279.0	0.80/380.0	0.80/615.0	0.80/927.0
BV-Series w/liner ^(Note 3)	Liquid				2.45/0.57	2.45/1.44	2.45/2.24	2.45/5.41	2.45/9.62	2.45/23.7	2.45/44.1	2.45/70.8	2.45/101.0							
BV-Series w/liner ^(Note 3)	Gas				0.80/0.57	0.80/1.44	0.55/2.24	0.80/5.41	0.80/9.62	0.80/23.7	0.80/44.1	0.80/70.8	0.80/101.0							
Scored B, XB, & "SCD B"	Liquid				0.40/0.86	0.40/2.03	0.40/3.35	0.40/7.39	0.40/12.7	0.40/28.8	0.40/50.0	0.40/78.8	0.40/111.0	0.40/137.0	0.40/176.0	0.40/223.0	0.40/277.0	0.40/402.2		
Scored B, XB, & "SCD B"	Gas				0.40/0.86	0.40/2.03	0.40/3.35	0.40/7.39	0.40/12.7	0.40/28.8	0.40/50.0	0.40/78.8	0.40/111.0	0.40/137.0	0.40/176.0	0.40/223.0	0.40/277.0	0.40/402.2		
Scored B, XB, & "SCD B"-LTF ^(Note 5)	Liquid				4.77/0.80	4.77/1.76	4.77/3.33	4.77/6.51	4.77/11.82	4.77/28.8	4.77/49.9	4.77/78.9	4.77/112.5	4.77/137.9	4.77/182.7	4.77/233.7	4.77/291.0	4.77/424.6		
Scored B, XB, & "SCD B"-LTF ^(Note 5)	Gas				4.77/0.80	4.77/1.76	4.77/3.33	4.77/6.51	4.77/11.82	4.77/28.8	4.77/49.9	4.77/78.9	4.77/112.5	4.77/137.9	4.77/182.7	4.77/233.7	4.77/291.0	4.77/424.6		
D, DR, DRR	Liquid				1.3/0.80	1.3/1.76	1.3/3.33	1.3/6.51	1.3/11.8	1.3/28.8	1.3/49.8	1.3/78.8	1.3/112.0	1.3/137.0	1.3/182.0	1.3/233.0	1.3/291.0	1.3/424.0	1.3/671.0	1.3/975.0
D, DR, DRR	Gas				1.19/0.69	1.19/1.62	1.19/2.95	1.19/6.49	1.19/11.0	1.19/25.9	1.19/47.1	1.19/74.6	1.19/106.0	1.19/135.0	1.19/176.0	1.19/223.0	1.19/277.0	1.19/397.0	1.19/661.0	1.19/907.0
D-,DR-, DRR-LTF ^(Note 5)	Liquid				2.3/0.80	2.3/1.76	2.3/3.33	2.3/6.51	2.3/11.8	2.3/28.8	2.3/49.8	2.3/78.8	2.3/112.0	2.3/137.0	2.3/182.0	2.3/223.0	2.3/291.0	2.3/424.0	2.3/671.0	2.3/975.0
D-,DR-, DRR-LTF ^(Note 5)	Gas				2.3/0.80	2.3/1.76	2.3/3.33	2.3/6.51	2.3/11.8	2.3/28.8	2.3/49.8	2.3/78.8	2.3/112.0	2.3/137.0	2.3/182.0	2.3/223.0	2.3/291.0	2.3/424.0	2.3/671.0	2.3/975.0
DV, DRV, DSV, DRSV	Liquid				2.60/0.57	2.60/1.44	2.60/2.24	2.60/5.41	2.60/9.62	2.60/23.7	2.60/44.1	2.60/70.8	2.60/101.0	2.60/130.0	2.60/176.0	2.60/202.0	2.60/280.0	2.60/380.0	2.60/615.0	2.60/927.0
DV, DRV, DSV, DRSV	Gas				1.19/0.69	1.19/1.62	1.19/2.94	1.19/6.49	1.19/11.0	1.19/25.9	1.19/47.1	1.19/74.6	1.19/106.0	1.19/135.0	1.19/176.0	1.19/223.0	1.19/277.0	1.19/397.0	1.19/660.0	1.19/907.0
PLD	Liquid				4.2/0.69	4.2/1/62	4.2/2.95	4.2/6.49	4.2/11/0	4.2/25.9	4.2/47.1	4.2/74.6	4.2/106.0	4.2/135.0	4.2/176.0	4.2/223.0	4.2/277.0	4.2/397.0	4.2/661.0	4.2/907.0
PLD	Gas				4.2/0.69	4.2/1/62	4.2/2.95	4.2/6.49	4.2/11/0	4.2/25.9	4.2/47.1	4.2/74.6	4.2/106.0	4.2/135.0	4.2/176.0	4.2/223.0	4.2/277.0	4.2/397.0	4.2/661.0	4.2/907.0
PLDV	Liquid				6.0/0.57	6.0/1.44	6.0/2.24	6.0/5.41	6.0/9.62	6.0/23.7	6.0/44.1	6.0/70.8	6.0/101.0	6.0/130.0	6.0/176.0	6.0/202.0	6.0/270.0	6.0/375.0	6.0/650.0	6.0/900.0
PLDV	Gas				6.0/0.57	6.0/1.44	6.0/2.24	6.0/5.41	6.0/9.62	6.0/23.7	6.0/44.1	6.0/70.8	6.0/101.0	6.0/130.0	6.0/176.0	6.0/202.0	6.0/270.0	6.0/375.0	6.0/650.0	6.0/900.0
AV	Liquid				4.35/0.86	4.35/2.03	4.35/3.35	4.35/7.39	4.35/12.7	4.35/28.8	4.35/50.0	4.35/78.8	4.35/113.0	4.35/137.0	4.35/182.0	4.35/233.0	4.35/291.0	4.35/424.0	4.35/671.0	4.35/975.0
AV	Gas				4.35/0.86	4.35/2.03	4.35/3.35	4.35/7.39	4.35/12.7	4.35/28.8	4.35/50.0	4.35/78.8	4.35/113.0	4.35/137.0	4.35/182.0	4.35/233.0	4.35/291.0	4.35/424.0	4.35/671.0	4.35/975.0
AVV	Liquid				10.5/0.40	10.5/0.95	10.5/1.60	10.5/4.0	10.5/8.0	10.5/16.5	10.5/35.75	10.5/45.5	10.5/62.75	10.5/74.5	10.5/111.0	10.5/158.0	10.5/195.0	10.5/280.0	10.5/425.0	10.5/630.0
AVV	Gas				10.5/0.40	10.5/0.95	10.5/1.60	10.5/4.0	10.5/8.0	10.5/16.5	10.5/35.75	10.5/45.5	10.5/62.75	10.5/74.5	10.5/111.0	10.5/158.0	10.5/195.0	10.5/280.0	10.5/425.0	10.5/630.0
AV-E & AV-EL	Liquid				1.2/0.864	1.2/2.036	1.2/3.356	1.2/7.392	1.2/12.73	1.2/28.89	1.2/50.02	1.2/78.85	1.2/113.1	1.2/137.9	1.2/182.7	1.2/233.7	1.2/291.0	1.2/424.6	1.2/672.0	1.2/975.9
AV-E & AV-EL	Gas				1.2/0.864	1.2/2.036	1.2/3.356	1.2/7.392	1.2/12.73	1.2/28.89	1.2/50.02	1.2/78.85	1.2/113.1	1.2/137.9	1.2/182.7	1.2/233.7	1.2/291.0	1.2/424.6	1.2/672.0	1.2/975.9

General Note: All K_R testing is done using Schedule 40 pipe.

General Note: The data provided herein is valid only when the disk is installed in a safety head (holder) which was concurrently certified with the disk as a device. Contact BS&B for additional information.

General Note: Except for those items highlighted yellow (Note #3), the data provided is valid for pressures equal to or above the catalog minimum pressures.

(Note 1) Data Valid for Alloy 600 Material Of Construction Only (Contact BS&B for minimum burst pressures for which the data is valid) (Values apply to disk with and without liners)

(Note 2) Data applies to GCR-Series disks alone, with Fluoropolymer Liners and/or sensors; Applies to GFR-series without integral sensors.(Contact BS&B for minimum burst pressures for which the data is valid)

(Note 3) Contact BS&B for minimum burst pressures for which the data is valid.

(Note 4) Data is not valid for graphite rupture disks which are equipped with "High Temperature Assemblies"

(Note 5) "LTF" Data for these disks is valid only when installed in a BS&B Type "Lo-To-Flo" Safety Head.

(Note 6) The "connections" for the Sta-Kul disks are:

- A-2 1/2" Inlet x Free vented outlet
- A-4 3/8" Inlet x 1/2" SAE outlet
- A-6 1/2" MPT x 1/2" MPT
- A-10 1" MPT Inlet x Free Vented Outlet
- A-19 3/4" MPT Inlet x 3/4"; MPT Outlet

BS&B Safety Systems
K_R (Left of Slash)/Minimum Net Flow Area (Right of Slash)
Minimum Net Flow Area (MNFA) in Square Inches

Style	Media	Size																		
		0.5"	0.6875"	0.75"	1.0"	1.5"	2.0"	3.0"	4.0"	6.0"	8.0"	10.0"	12.0"	14.0"	16.0"	18.0"	20.0"	24.0"	30.0"	36.0"
CSR (w/ or w/o Liners)	Liquid				3.19/0.86	3.19/2.03	3.19/3.35	3.19/7.39	3.19/12.7	3.19/28.8	3.19/50.0									
CSR (w/ or w/o Liners)	Gas				1.0/0.86	1.0/2.03	1.0/3.35	1.0/7.39	1.0/12.7	1.0/28.8	1.0/50.0									
CSI (w/ or w/o Liners)	Liquid				3.09/0.86	3.09/1.89	3.09/3.35	3.09/7.29	3.09/11.2	3.09/22.6	3.09/42.7	3.09/66.3								
CSI (w/ or w/o Liners)	Gas				0.62/0.86	0.62/1.89	0.62/3.35	0.62/7.29	0.62/11.2	0.62/22.6	0.62/42.7	0.62/66.3								
Sigma (Series)	Liquid				1.25/0.86	1.25/1.93	1.25/3.36	1.25/7.39	1.25/12.7	1.25/28.8	1.25/50.0									
Sigma (Series)	Gas				0.38/0.86	0.38/1.93	0.38/3.36	0.38/7.39	0.38/12.7	0.38/28.8	0.38/50.0									
UBR	Liquid				1.25/0.86	1.25/1.93	1.25/3.36	1.25/7.39	1.25/12.7	1.25/28.8	1.25/50.0									
UBR	Gas				0.38/0.86	0.38/1.93	0.38/3.36	0.38/7.39	0.38/12.7	0.38/28.8	0.38/50.0									
LPS & LPS Welded Assembly	Liquid				0.86/0.86	0.86/1.93	0.86/3.36	0.86/7.39	0.86/12.7	0.86/28.8	0.86/50.0	0.86/78.8	0.86/111.8							
LPS & LPS Welded Assembly	Gas				0.79/0.86	0.79/1.93	0.79/3.36	0.79/7.39	0.79/12.7	0.79/28.8	0.79/50.0	0.79/78.8	0.79/111.8							
LPS-U	Liquid	1.22/0.304		0.93/0.533	1.7/0.608															
LPS-U	Gas	1.06/0.304		0.89/0.533	1.7/0.608															
S-90 (w/ or w/o Liners & S-90 Welded Assys)	Gas				1.13/0.86	1.13/2.03	1.13/3.36	1.13/7.39	1.13/12.7	1.13/28.8	1.13/50.0	1.13/78.8	1.13/111.0	1.13/135.0	1.13/176.0	1.13/223.0	1.13/277.0	1.13/402.0	1.13/672.0	
S-90 (Note 1)	Gas				0.23/0.86	0.23/2.03	0.23/3.36	0.23/7.39	0.23/12.7	0.23/28.8	0.23/50.0	0.23/78.8	0.23/111.0	0.23/135.0	0.23/176.0	0.23/223.0	0.23/277.0	0.23/402.0	0.23/672.0	
S-90 Double Disk Assembly	Gas				1.13/0.86	1.13/2.03	1.13/3.35	1.13/7.39	1.13/12.7	1.13/28.8	1.13/50.0	1.13/78.8	1.13/111.0	1.13/135.0	1.13/176.0	1.13/223.0	1.13/277.0	1.13/402.0	1.13/672.0	
SVI	Gas					11.35/1.37	11.35/2.26	11.35/5.11	11.35/8.66	11.35/20.9	11.35/37.0	11.35/61.0								
MVB	Gas							0.23/7.39												
SRC (Note 3)	Gas						1.1/3.35	1.1/7.39	1.1/12.7	1.1/28.8	1.1/50.0									
JRS	Gas				0.31/0.86	0.31/1.89	0.31/3.35	0.31/6.53	0.31/11.86	0.31/25.08	0.31/42.07	0.31/68.65	0.31/102.28	0.31/121.86	0.31/156.0	0.31/198.0	0.31/246.0	0.31/357.0	0.31/592.0	0.31/868.0
RLS (w/ or w/o Liners & Welded Assy)	Liquid			5.83/0.50	5.83/0.84	5.83/1.77	5.83/3.23	5.83/6.44	5.83/11.5	5.83/26.4	5.83/47.0	5.83/73.9	5.83/99.0	5.83/131.0	5.83/172.0	5.83/219.0	5.83/270.0			
RLS (w/ or w/o Liners & Welded Assy)	Gas		1.14/0.50		1.14/0.84	1.14/1.77	1.14/3.23	1.14/6.44	1.14/11.5	1.14/26.4	1.14/47.0	1.14/73.9	1.14/99.0	1.14/131.0	1.14/172.0	1.14/219.0	1.14/270.0			
RLS Double Disk Assembly	Liquid				5.83/0.84	5.83/1.77	5.83/3.23	5.83/6.44	5.83/11.5	5.83/26.4	5.83/47.0	5.83/73.9	5.83/99.0	5.83/131.0	5.83/172.0	5.83/219.0	5.83/270.0			
RLS Double Disk Assembly	Gas				1.9/0.84	1.9/1.77	1.9/3.23	1.9/6.44	1.9/11.5	1.9/26.4	1.9/47.0	1.9/73.9	1.9/99.0	1.9/131.0	1.9/172.0	1.9/219.0	1.9/270.0			
SK _R & SKR Welded Assy.	Liquid			1.90/0.59	1.90/0.86	1.90/2.04	1.90/3.36	1.90/7.39	1.90/12.74	1.90/28.89	1.90/50.0	1.90/78.86	1.90/111.87							
SK _R & SKR Welded Assy.	Gas			0.37/0.59	0.37/0.86	0.37/2.04	0.37/3.36	0.37/7.39	0.37/12.74	0.37/28.89	0.37/50.0	0.37/78.86	0.37/111.87							
SK _R -U	Liquid			1.10/0.53	2.20/0.61															
SK _R -U	Gas	0.85/0.30		0.73/0.53	1.25/0.61															
SKr Double Disk Assembly	Liquid			1.6/0.59	1.6/0.86	1.6/2.04	1.6/3.36	1.6/7.39	1.6/12.74	1.6/28.89	1.6/50.0	1.6/78.86	1.6/111.87							
SKR Double Disk Assembly	Gas			0.63/0.59	0.63/0.86	0.63/2.04	0.63/3.36	0.63/7.39	0.63/12.74	0.63/28.89	0.63/50.0	0.63/78.86	0.63/111.87							
SKI & SKI-TN	Liquid				1.03/0.86	1.03/1.93	1.03/3.36	1.03/7.39	1.03/12.74	1.03/28.89	1.03/50.0									
SKI & SKI-TN	Gas				0.47/0.86	0.47/1.93	0.47/3.36	0.47/7.39	0.47/12.74	0.47/28.89	0.47/50.0									
SSR	Liquid				0.52/0.86	0.52/1.93	0.52/3.36	0.52/7.39	0.52/12.74	0.52/28.89	0.52/50.0	0.52/78.8								
SSR	Gas				0.52/0.86	0.52/1.93	0.52/3.36	0.52/7.39	0.52/12.74	0.52/28.89	0.52/50.0	0.52/78.8								
SRD	Liquid				4.0/0.84	4.0/1.77	4.0/3.23	4.0/6.44	4.0/11.54	4.0/26.44	4.0/47.07									
SRD	Gas				0.59/0.84	0.59/1.77	0.59/3.23	0.59/6.44	0.59/11.54	0.59/26.44	0.59/47.07									

General Note: All K_R testing is done using Schedule 40 pipe.

General Note: The data provided herein is valid only when the disk is installed in a safety head (holder) which was concurrently certified with the disk as a device. Contact BS&B for additional information.

General Note: Except for those items highlighted yellow (Note #3), the data provided is valid for pressures equal to or above the catalog minimum pressures.

(Note 1) Data Valid for Alloy 600 Material Of Construction Only (Contact BS&B for minimum burst pressures for which the data is valid) (Values apply to disk with and without liners)

(Note 2) Data applies to GCR-Series disks alone, with Fluoropolymer Liners and/or sensors; Applies to GFR-series without integral sensors.(Contact BS&B for minimum burst pressures for which the data is valid)

(Note 3) Contact BS&B for minimum burst pressures for which the data is valid.

(Note 4) Data is not valid for graphite rupture disks which are equipped with "High Temperature Assemblies"

(Note 5) "LTF" Data for these disks is valid only when installed in a BS&B Type "Lo-To-Flo" Safety Head.

(Note 6) The "connections" for the Sta-Kul disks are:

- A-2 1/2" Inlet x Free vented outlet
- A-4 3/8" Inlet x 1/2" SAE outlet
- A-6 1/2" MPT x 1/2" MPT
- A-10 1" MPT Inlet x Free Vented Outlet
- A-19 3/4" MPT Inlet x 3/4"; MPT Outlet

BS&B Safety Systems
K_R (Left of Slash)/Minimum Net Flow Area (Right of Slash)
Minimum Net Flow Area (MNFA) in Square Inches

Style	Media	Size																		
		0.5"	0.6875"	0.75"	1.0"	1.5"	2.0"	3.0"	4.0"	6.0"	8.0"	10.0"	12.0"	14.0"	16.0"	18.0"	20.0"	24.0"	30.0"	36.0"
SRD-L	Liquid				4.5/0.84	4.5/1.77	4.5/3.23	4.5/6.44	4.5/11.54	4.5/26.44	4.5/47.07									
SRD-L	Gas				3.4/0.84	3.4/1.77	3.4/3.23	3.4/6.44	3.4/11.54	3.4/26.44	3.4/47.07									
CCS	Liquid				4.0/0.84	4.0/1.77	4.0/3.23	4.0/6.44	4.0/11.54	4.0/26.44	4.0/47.07									
CCS	Gas				0.59/0.84	0.59/1.77	0.59/3.23	0.59/6.44	0.59/11.54	0.59/26.44	0.59/47.07									
CCS-L	Liquid				4.5/0.84	4.5/1.77	4.5/3.23	4.5/6.44	4.5/11.54	4.5/26.44	4.5/47.07									
CCS-L	Gas				3.4/0.84	3.4/1.77	3.4/3.23	3.4/6.44	3.4/11.54	3.4/26.44	3.4/47.07									
FRS	Gas				0.80/0.86	0.80/1.93	0.80/3.35													
FRS w/liner ^(Note 3)	Gas				0.80/0.86	0.80/1.93	0.80/3.35													
ECR	Liquid		(Not Tested)																	
ECR	Gas				0.58/0.86	0.58/2.03	0.58/3.35	0.58/7.30	0.58/12.1	0.58/25.4	0.58/43.6	0.58/66.3	0.58/94.7	0.58/118.0	0.58/154.0	0.58/195.0	0.58/241.0	0.58/348.0		
ECV	Gas				4.2/0.735	4.2/1.24	4.2/2.21	4.2/4.76	4.2/7.9	4.2/18.1	4.2/31.4	4.2/48.8	4.2/69.4	4.2/88.0	4.2/115.0	4.2/146.0	4.2/180.0	4.2/261.0		
RB-90	Gas				3.47/0.83	3.47/1.80	3.47/3.15	3.47/6.84	3.47/11.84	3.47/25.44	3.47/47.6	3.47/67.6	3.47/101.8	3.47/121.6	3.47/162.7	3.47/209.9	3.47/262.9	3.47/386.8	3.47/617.6	3.47/872.8
MRB	Gas		5.3/0.14		5.3/0.55	5.3/1.24	5.3/2.20	5.3/4.50	5.3/8.80	5.3/19.8	5.3/35.2	5.3/55.0								
GFN (w/ or w/o Liners)	Gas				0.55/0.864	0.55/2.03	0.55/3.36	0.55/7.39	0.55/12.7	0.55/28.9	0.55/50.0	0.55/78.8	0.55/111.9	0.55/137.9	0.55/176.7	0.55/223.3	0.55/277.9	0.55/402.0		
XT ^(Note 3)	Liquid				0.5/0.86	0.5/2.03	0.5/3.36	0.5/7.39	0.5/12.7	0.5/28.8	0.5/50.0	0.5/78.8	0.5/111.0							
XT ^(Note 3)	Gas				0.5/0.86	0.5/2.03	0.5/3.36	0.5/7.39	0.5/12.7	0.5/28.8	0.5/50.0	0.5/78.8	0.5/111.0							
MB, AMB ^(Note 4)	Liquid				0.19/0.86	0.19/2.03	0.19/3.35	0.19/7.39	0.19/12.7	0.19/28.8	0.19/50.0	0.19/78.8	0.19/113.0	0.19/137.0	0.19/182.0	0.19/233.0	0.19/291.0	0.19/424.0		
MB, AMB ^(Note 4)	Gas				0.19/0.86	0.19/2.03	0.19/3.35	0.19/7.39	0.19/12.7	0.19/28.8	0.19/50.0	0.19/78.8	0.19/113.0	0.19/137.0	0.19/182.0	0.19/233.0	0.19/291.0	0.19/424.0		
MBV, AMBV (bar spt) ^(Note 4)	Liquid				1.9/0.63	1.9/1.66	1.9/2.69	1.9/5.92	1.9/10.4	1.9/23.1	1.9/40.9	1.9/63.7	1.9/91.5	1.9/110.0	1.9/146.0	1.9/186.0	1.9/232.0	1.9/339.0		
MBV, AMBV (bar spt) ^(Note 4)	Gas				1.9/0.63	1.9/1.66	1.9/2.69	1.9/5.92	1.9/10.4	1.9/23.1	1.9/40.9	1.9/63.7	1.9/91.5	1.9/110.0	1.9/146.0	1.9/186.0	1.9/232.0	1.9/339.0		
MBV, AMBV (dial spt) ^(Note 4)	Liquid				5.40/0.298	5.40/1.02	5.40/1.74	5.40/4.20	5.40/7.60	5.40/15.8	5.40/25.8	5.40/41.0	5.40/59.1	5.40/88.3	5.40/95.7	5.40/124.0	5.40/153.0	5.40/226.0		
MBV, AMBV (dial spt) ^(Note 4)	Gas				5.40/0.298	5.40/1.02	5.40/1.74	5.40/4.20	5.40/7.60	5.40/15.8	5.40/25.8	5.40/41.0	5.40/59.1	5.40/88.3	5.40/95.7	5.40/124.0	5.40/153.0	5.40/226.0		
IMB, AIBM, FSM, AFSM ^(Note 4)	Liquid				0.31/0.86	0.31/2.03	0.31/3.35	0.31/7.39	0.31/12.7	0.31/28.8	0.31/50.0	0.31/78.8	0.31/113.0	0.31/137.0	0.31/182.0	0.31/233.0	0.31/291.0	0.31/424.0		
IMB, AIBM, FSM, AFSM ^(Note 4)	Gas				0.31/0.86	0.31/2.03	0.31/3.35	0.31/7.39	0.31/12.7	0.31/28.8	0.31/50.0	0.31/78.8	0.31/113.0	0.31/137.0	0.31/182.0	0.31/233.0	0.31/291.0	0.31/424.0		
IMBL, AIMBL ^(Note 4)	Liquid				0.31/0.86	0.31/2.03	0.31/3.35	0.31/7.39	0.31/12.7	0.31/28.8	0.31/50.0	0.31/78.8	0.31/113.0	0.31/137.0	0.31/182.0	0.31/233.0	0.31/291.0	0.31/424.0		
IMBL, AIMBL ^(Note 4)	Gas				0.31/0.86	0.31/2.03	0.31/3.35	0.31/7.39	0.31/12.7	0.31/28.8	0.31/50.0	0.31/78.8	0.31/113.0	0.31/137.0	0.31/182.0	0.31/233.0	0.31/291.0	0.31/424.0		
RE, REA ^(Note 4)	Liquid				0.15/0.86	0.15/2.03	0.15/3.35	0.15/7.39	0.15/12.7	0.15/28.8	0.15/50.0	0.15/78.8	0.15/113.0	0.15/137.0	0.15/182.0	0.15/233.0	0.15/291.0	0.15/424.0		
RE, REA ^(Note 4)	Gas				0.15/0.86	0.15/2.03	0.15/3.35	0.15/7.39	0.15/12.7	0.15/28.8	0.15/50.0	0.15/78.8	0.15/113.0	0.15/137.0	0.15/182.0	0.15/233.0	0.15/291.0	0.15/424.0		
REV, REVA ^(Note 4)	Liquid				3.15/0.69	3.15/1.76	3.15/3.09	3.15/6.29	3.15/10.2	3.15/20.9	3.15/37.1	3.15/56.5	3.15/77.5	3.15/99.1	3.15/125.0	3.15/158.0	3.15/190.0	3.15/269.0		
REV, REVA ^(Note 4)	Gas				3.15/0.69	3.15/1.76	3.15/3.09	3.15/6.29	3.15/10.2	3.15/20.9	3.15/37.1	3.15/56.5	3.15/77.5	3.15/99.1	3.15/125.0	3.15/158.0	3.15/190.0	3.15/269.0		
REL, RELA ^(Note 4)	Liquid				0.16/0.86	0.16/2.03	0.16/3.35	0.16/7.39	0.16/12.7	0.16/28.8	0.16/50.0	0.16/78.8	0.16/113.0	0.16/137.0	0.16/182.0	0.16/233.0	0.16/291.0	0.16/424.0		
REL, RELA ^(Note 4)	Gas				0.16/0.86	0.16/2.03	0.16/3.35	0.16/7.39	0.16/12.7	0.16/28.8	0.16/50.0	0.16/78.8	0.16/113.0	0.16/137.0	0.16/182.0	0.16/233.0	0.16/291.0	0.16/424.0		

General Note: All K_R testing is done using Schedule 40 pipe.

General Note: The data provided herein is valid only when the disk is installed in a safety head (holder) which was concurrently certified with the disk as a device. Contact BS&B for additional information.

General Note: Except for those items highlighted yellow (Note #3), the data provided is valid for pressures equal to or above the catalog minimum pressures.

(Note 1) Data Valid for Alloy 600 Material Of Construction Only (Contact BS&B for minimum burst pressures for which the data is valid) (Values apply to disk with and without liners)

(Note 2) Data applies to GCR-Series disks alone, with Fluoropolymer Liners and/or sensors; Applies to GFR-series without integral sensors.(Contact BS&B for minimum burst pressures for which the data is valid)

(Note 3) Contact BS&B for minimum burst pressures for which the data is valid.

(Note 4) Data is not valid for graphite rupture disks which are equipped with "High Temperature Assemblies"

(Note 5) "LTF" Data for these disks is valid only when installed in a BS&B Type "Lo-To-Flo" Safety Head.

(Note 6) The "connections" for the Sta-Kul disks are:

- A-2 1/2" Inlet x Free vented outlet
- A-4 3/8" Inlet x 1/2" SAE outlet
- A-6 1/2" MPT x 1/2" MPT
- A-10 1" MPT Inlet x Free Vented Outlet
- A-19 3/4" MPT Inlet x 3/4"; MPT Outlet

BS&B Safety Systems
K_R (Left of Slash)/Minimum Net Flow Area (Right of Slash)
Minimum Net Flow Area (MNFA) in Square Inches

Style	Media	Size																			
		0.5"	0.6875"	0.75"	1.0"	1.5"	2.0"	3.0"	4.0"	6.0"	8.0"	10.0"	12.0"	14.0"	16.0"	18.0"	20.0"	24.0"	30.0"	36.0"	
GFR-Series ^(Note 2)	Liquid				19.14/0.20	11.5/0.79	4.76/1.77														
GFR-Series ^(Note 2)	Gas				19.14/0.20	9.92/0.79	4.76/1.77	23.47/4.91													
GCR-Series ^(Note 2)	Liquid					2.75/1.5	1.42/2.7	2.75/5.29	2.75/9.78												
GCR-Series ^(Note 2)	Gas					1.95/1.5	1.25/2.7	1.95/5.29	1.95/9.78												
GCR-N (Series) ^(Note 2)	Liquid					2.75/1.5	1.42/2.7														
GCR-N (Series) ^(Note 2)	Gas					1.95/1.5	1.25/2.7														
SLP-Series	Liquid					6.70/1.08	4.9/2.04	9.9/3.55													
SLP-Series	Gas					6.70/1.08	4.9/2.04	9.9/3.55													
GLP-S ^(Note 3)	Gas					10.0/0.86	10.0/1.93	10.0/3.36	10.0/7.39												
A-2 Sta-Kul w/ FRB disk ^{(Note 3)(Note 6)}	Gas	2.20/0.19																			
A-6 Sta-Kul, FRB disk ^(Note 6)	Gas	2.19/0.19																			
A-10 Sta-Kul w/ Scored "B" ^(Note 6)	Gas				0.41/0.78																
Sta-Kul, B disk; 3/4"	Gas			3.85/0.44																	
FRB WFT	Gas	35.7/0.21																			
A-6 Sta-Kul, "B" ^{(Note 3)(Note 6)}	Gas		6.44/0.19																		
A-6 Sta-Kul, "B" (w/ liner) ^{(Note 3)(Note 6)}	Gas		6.44/0.19																		
A-19 Sta-Kul w/ Scored "B" ^(Note 6)	Gas			0.50/0.44																	
FRB w/ 3/4" San'y Connect ^(Note 3)	Gas/Liquid			12.0/0.22																	
FRB w/ 3/4" San'y Connect ^(Note 3)	Gas			5.9/0.22																	
1" Welded FRB w/ 1/2" VCR Conn.	Gas	16.95/0.126		5.0/0.20																	

General Note: All K_R testing is done using Schedule 40 pipe.

General Note: The data provided herein is valid only when the disk is installed in a safety head (holder) which was concurrently certified with the disk as a device. Contact BS&B for additional information.

General Note: Except for those items highlighted yellow (Note #3), the data provided is valid for pressures equal to or above the catalog minimum pressures.

(Note 1) Data Valid for Alloy 600 Material Of Construction Only (Contact BS&B for minimum burst pressures for which the data is valid) (Values apply to disk with and without liners)

(Note 2) Data applies to GCR-Series disks alone, with Fluoropolymer Liners and/or sensors; Applies to GFR-series without integral sensors.(Contact BS&B for minimum burst pressures for which the data is valid)

(Note 3) Contact BS&B for minimum burst pressures for which the data is valid.

(Note 4) Data is not valid for graphite rupture disks which are equipped with "High Temperature Assemblies"

(Note 5) "LTF" Data for these disks is valid only when installed in a BS&B Type "Lo-To-Flo" Safety Head.

(Note 6) The "connections" for the Sta-Kul disks are:

A-2 1/2" Inlet x Free vented outlet

A-4 3/8" Inlet x 1/2" SAE outlet

A-6 1/2" MPT x 1/2" MPT

A-10 1" MPT Inlet x Free Vented Outlet

A-19 3/4" MPT Inlet x 3/4"; MPT Outlet